

SAFETY DATA SHEET

Issuing Date 09-Jan-2013

Revision Date 17-Dec-2015

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name New Skin Liquid Bandage

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Medicinal products

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name MEDTECH PRODUCTS INC

Supplier Address 660 White Plains Road
Tarrytown, NY 10591
USA

Supplier Phone Number Phone:1-864-879-0953
Fax:1-914-524-6815
Contact Phone914-524-6861

Supplier Email bodongo@prestigebrandsinc.com

Emergency telephone number

Company Emergency Phone Number 1-864-879-0953

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

GHS Label elements, including precautionary statements



Emergency Overview

Signal word		Danger	
Hazard Statements			
Causes serious eye irritation			
May cause an allergic skin reaction			
May cause drowsiness or dizziness			
Highly flammable liquid and vapor			
			
Appearance		Physical state	Odor
Clear, colorless to yellow/orange		Liquid	Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool
Wear eye/face protection

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Harmful to aquatic life

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Ethyl acetate	141-78-6	30 - 60	*
Butyl acetate	123-86-4	10 - 30	*
Amyl acetate	628-63-7	10 - 30	*
Ethanol	64-17-5	3 - 7	*
Nitrocellulose	9004-70-0	1 - 5	*
Camphor	464-48-2	1 - 5	*
Benzethonium Chloride	498-77-1	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

Show this safety data sheet to the doctor in attendance.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact

May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water

while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed**Most Important Symptoms and Effects**

Burning sensation. Itching. Rashes. Hives. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

May cause sensitization of susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Dry chemical, CO₂, water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Some may be transported hot.

Uniform Fire Code

Flammable Liquid: I-B

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. See section 8 for more information. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for containment

A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong oxidizing agents. Acids. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Amyl acetate 628-63-7	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 525 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 525 mg/m ³
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm 10% LEL TWA: 1000 ppm TWA: 1900 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists – Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration – Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

None required for consumer use. If there is a risk of contact: Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid	Odor	Solvent
Appearance	Viscous liquid	Odor Threshold	No information available
Color	Clear, colorless to yellow/orange		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	78 °C / 172 °F	None known	
Flash Point	-4 C / 24 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	0.9	None known	
Water Solubility	Partially soluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Acids. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness and dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acetate 141-78-6	= 5620 mg/kg (Rat)	> 20 mL/kg (Rabbit)	-
Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Ethanol 64-17-5	-	-	= 124.7 mg/L (Rat) 4 h
Camphor 464-48-2	=1310 mg/kg (Mouse)	-	-
Benzethonium Chloride 498-77-1	=295 mg/kg (Rat) = 338 mg/kg (Mouse)	-	-

Information on toxicological effects

Symptoms	May cause redness and tearing of the eyes. Itching. Rashes. Hives. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	May cause sensitization of susceptible persons. May cause sensitization by skin contact.
Mutagenic Effects	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethanol 64-17-5	A3	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 – Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 – Carcinogenic to Humans

Group 3 – Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known – Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X – Present

Reproductive toxicity	No information available.
------------------------------	---------------------------

STOT – single exposure	No information available.
STOT – repeated exposure	No information available.
Chronic Toxicity	Contains a known or suspected carcinogen. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected reproductive toxin. Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.
Target Organ Effects	Central Nervous System (CNS). Eyes. Respiratory system. Skin. Blood. Liver. Reproductive System. Kidney. Spleen. Systemic Toxicity. Lungs.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

8,349.00 mg/kg

ATEmix (inhalation-dust/mist)

1,936.30 mg/l

ATEmix (inhalation-vapor)

911.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethyl acetate 141-78-6	48h EC50: = 3300 mg/L (Desmodesmus subspicatus)	96h LC50: 220 – 250 mg/L (Pimephales promelas) 96h LC50: 352 – 500 mg/L (Oncorhynchus mykiss) 96h LC50: = 484 mg/L (Oncorhynchus mykiss)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	48h EC50: = 560 mg/L
Butyl acetate 123-86-4	72h EC50: = 674.7 mg/L (Desmodesmus subspicatus)	96h LC50: 17 – 19 mg/L (Pimephales promelas) 96h LC50: = 62 mg/L (Leuciscus idus) 96h LC50: = 100 mg/L (Lepomis macrochirus)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	24h EC50: = 72.8 mg/L
Amyl acetate 628-63-7		96h LC50: = 650 mg/L (Lepomis macrochirus)		
Ethanol 64-17-5		96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 13400 – 15100 mg/L (Pimephales promelas) 96h LC50: 12.0 – 16.0 mL/L (Oncorhynchus mykiss)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	48h LC50: 9268 – 14221 mg/L 48h EC50: = 2 mg/L 24h EC50: = 10800 mg/L
Camphor 464-48-2		LC50 - Pimephales promelas (fathead minnow) - 17 mg/l - 96 h		
Benzethonium Chloride 498-77-1		1.6 mg/l LC50 96 h Pimephales promelas 1.4 mg/l LC50 96 h Lepomis macrochirus		

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Ethyl acetate 141-78-6	0.6
Butyl acetate 123-86-4	1.81
Ethanol 64-17-5	-0.32

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Should not be released into the environment. Dispose of contents/containers in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethyl acetate 141-78-6		Included in waste stream: F039		U112

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethyl acetate 141-78-6	Toxic Ignitable
Butyl acetate 123-86-4	Toxic
Amyl acetate 628-63-7	Toxic Ignitable
Ethanol 64-17-5	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Description CONSUMER COMMODITY, ORM-D
Emergency Response Guide Number 128

TDG

UN-No. UN1993
Proper Shipping Name FLAMMABLE LIQUID, N.O.S.
Hazard Class 3
Packing Group II
Description UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATE), 3, II

MEX

UN-No. UN1993
Proper Shipping Name FLAMMABLE LIQUIDS, N.O.S.
Hazard Class 3
Packing Group II
Description UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATE), 3, II

ICAO

UN-No.	UN1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Hazard Class	3
Packing Group	II
Description	UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATE), 3, II

IATA

UN-No.	UN1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Hazard Class	3
Packing Group	II
Description	UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATE), 3, II

IMDG/IMO

UN-No.	UN1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Hazard Class	3
Packing Group	II
EmS-No.	F-E, S-E
Description	UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATE), 3, II, FP -4.4C

RID

UN-No.	UN1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATE), 3, II

ADR

UN-No.	UN1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATE), 3, II

ADN

UN-No.	UN1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.
Hazard Class	3
Packing Group	II
Classification code	F1
Special Provisions	274, 601, 640D
Description	UN1993, FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATE), 3, II
Hazard Labels	3
Limited Quantity	LQ4
Ventilation	VE01

15. REGULATORY INFORMATION**International Inventories**

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains no chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl acetate 123-86-4	5000 lb			X
Amyl acetate 628-63-7	5000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethyl acetate 141-78-6	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Amyl acetate 628-63-7	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals. Ethyl alcohol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage.

Chemical Name	California Proposition 65
Ethanol - 64-17-5	Carcinogen Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Ethyl acetate 141-78-6	X	X	X	X	
Butyl acetate 123-86-4	X	X	X	X	
Amyl acetate	X	X	X	X	

628-63-7					
Nitrocellulose 9004-70-0	X	X	X		X

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Ethyl acetate 141-78-6 (30 - 60)		Mexico: TWA= 400 ppm Mexico: TWA= 1400 mg/m ³
Butyl acetate 123-86-4 (10 - 30)		Mexico: TWA 150 ppm Mexico: TWA 710 mg/m ³ Mexico: STEL 200 ppm Mexico: STEL 950 mg/m ³
Amyl acetate 628-63-7 (10 - 30)		Mexico: TWA 100 ppm Mexico: TWA 530 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 800 mg/m ³
Ethanol 64-17-5 (3 - 7)		Mexico: TWA 1000 ppm Mexico: TWA 1900 mg/m ³

*Mexico - Occupational Exposure Limits - Carcinogens***Canada****WHMIS Hazard Class**

Not determined

16. OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 2	Flammability 3	Physical Hazard 0	Personal Protection X

Prepared By

Prestige Brands
660 White Plains Rd.
Tarrytown, Ny 10591

Issuing Date

09-Jan-2013

Revision Date

17-Dec-2015

Revision Note

Formula change

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet